

Mondrian® Plus 60 Small Rectangle Paver



Do not use vibrating plate



1 bag of sand covers approx. 38 ft²



Pedestrian - Designed to withstand pedestrian traffic



Vehicular - Designed to withstand car traffic


Mondrian® Plus 60 Small Rectangle Paver




	DIMENSIONS (MM)	DIMENSIONS (IN)
	60 x 330 x 165	2 3/8 x 13 x 6 1/2
Weight/unit	7.7 kg	17 lb
Unit/surface	18.52 unit/m ²	1.71 unit/ft ²
Area/layer	0.82 m ²	8.79 ft ²
Area/cube	9.84 m²	12 Rows
Length/row Soldier	2.48 lin. m	8.12 lin. ft
Length/cube Soldier	29.76 lin. m	97.44 lin. ft
Qty/cube	180 units	180 units
Weight/cube	1389 kg	3062 lb

CODES	COLOURS
PRESTIGE COLOURS	
12052557	Rockland Black
Sold in full cubes only	
Production location Bolton	


TYPICAL ROW



LAYING PATTERNS



Linear



Herringbone

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Small Rectangle Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.

The Mondrian Plus 60 slab is compatible with the Mondrian Plus 60 small rectangle paver for non-vehicular application only.