

BRISTOL VALLEY[®] 80mm

ENDURACOLOR™



GRANITE FUSION

OAK BROWN FUSION **NEW**

VISUAL APPEARANCE

Gentle surface clefts and waved edges.


FINISH

The subtle surface texture and understated edge detail of Bristol Valley[®] brings a refined elegance to projects where a more commonplace flagstone slab may have been used in the past.

PRODUCT SPECIFICATIONS



LARGE RECTANGLE
15 x 22½ x 3⅛"
380 x 570 x 80 mm



SQUARE
15 x 15 x 3⅛"
380 x 380 x 80mm



SMALL RECTANGLE
7½ x 15 x 3⅛"
190 x 380 x 80mm

3 UNIT RANDOM BUNDLE


EDGE DETAILS



WAVED EDGE


BUNDLE CONFIGURATION

BRISTOL VALLEY
RANDOM BUNDLE




LAYING PATTERNS

BRISTOL VALLEY
RANDOM A



BRISTOL VALLEY RANDOM A
40% Large Rectangle, 40%
Square, 20% Small Rectangle

BRISTOL VALLEY
RANDOM B



BRISTOL VALLEY RANDOM B
40% Large Rectangle, 40%
Square, 20% Small Rectangle

*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- C140 for Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

LEED INFORMATION

Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour

DRIVE FRIENDLY

80mm pavers can handle vehicular loads

Ask about our base stabilization system

PRODUCT DATA

Stones & Bundling	Unit		SqFt Per				Per Bundle		Soldier LnFt per			Sailor LnFt per			Units Per		Lbs Per		
	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Layer	Bundle	Unit	Layer	Bundle	SqFt	Layer	Bundle	Unit	Layer	Bundle
Pickering Manufacturing																			
Random Bundle		81.6	11.66	-	1.46	9	-	-	-	-	0.90	9.35	65.45	0.69	7	72	35.68	426.57	2,986.02
Large Rectangle	3 3/8" (80mm)	-	-	-	2.09	-	-	-	-	-	1.88	-	-	0.48	-	14	-	-	-
Square	3 3/8" (80mm)	-	-	-	1.40	-	-	-	-	-	1.25	-	-	1.43	-	21	-	-	-
Small Rectangle	3 3/8" (80mm)	-	-	-	0.70	-	-	-	-	-	0.63	-	-	0.72	-	21	-	-	-

Notes: Product sold in full bundles only on a refundable skid. All measurements are nominal. **Product is not intended for vehicular applications. Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



Pedestrian



Residential Vehicular



Commercial Vehicular



*Wall pairing suggestion- U-CARA® - matching colour and finish

RECOMMENDED SANDS

RECOMMENDED SEALER



Romex: Rompox® ECO-Fine
Pedestrian Applications only

- | Ready mixed and easy to use
- | Resin film free
- | Resistant to ants, weeds, de-icing salts
- | Made from 98% natural, recycled or renewable raw materials
- | Pressure washer safe
- | Ideal for joint widths from 5mm (1/4")

Coverage:

Colour	5-6mm Joints
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix



Romex: Rompox® D1
Vehicular Applications

- | Light to medium vehicle rated
- | Resistant to ants, weeds, frost & de-icing salts
- | Self-compacting and water emulsifiable
- | Ideal for joint widths from 3mm (1/4")
- | Ideal for driveways, parking spaces and all vehicular loading applications up to 7.5 T

Coverage:

Colour	7mm Joints
Neutral, Stone Grey, Basalt Two 1 L bottles to be mixed with one 55 lb bag of Romex approved sand	20 sqft / 55 lb mix (based on 1,000 sqft)



Alliance - Gator G2 MAXX Sand

- | Rain safe after 15 minutes (24hr no rain if concrete overlay)
- | Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation
- | Dust free and haze free
- | Requires only one watering
- | Four colours: Beige, Grey, Black and Ivory

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft
Black 50lb. bag	58-76 sqft	20-38 sqft



Alliance - Gator Natural Look Sealer

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L / 5.28 U.S. gal.	875 sqft

*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.