


Melville® 80 Textureguard Paver



Do not use vibrating plate



1 bag of sand covers approx. 116 ft²



Pedestrian - Designed to withstand pedestrian traffic



Vehicular - Designed to withstand car traffic


Melville® 80 Textureguard Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
A	80 x 190 x 380	3 1/8 x 7 1/2 x 15
B	80 x 380 x 380	3 1/8 x 15 x 15
C	80 x 380 x 570	3 1/8 x 15 x 22 7/16
Weight/unit (avg.)	27 kg	59 lb
Area/layer (moy.)	7.387 unit/m ²	0.686 unit/ft ²
Area/layer	1.08 m ²	11.66 ft ²
Area/cube	8.64 m²	8 Rows 93.28 ft²
Length/row Soldier	3.04 lin. m	9.97 lin. ft
Length/cube Soldier	24.32 lin. m	79.79 lin. ft
Weight/cube	1709 kg	3768 lb


CODES	COLOURS
10554893	Marbella
10555066	Silverstone
10555067	Hickory

Sold in full cubes only
Production location Metcalfe


TYPICAL ROW



LAYING PATTERNS



Linear



Modular

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 Textureguard Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.