

# COURTSTONE®

Exclusive to **JNILOCK**

**ELEGANCE**



BASALT

## VISUAL APPEARANCE

Each cobble is uniquely formed to closely resemble authentic European cobblestones.

## FINISH

Timeworn. Realta™ Technology provides ultra-realistic textures cast from brick, cobblestone or flagstone.

## PRODUCT SPECIFICATIONS



### **XL RECTANGLE**

5 1/8 x 8 3/8 x 2 3/8"  
130 x 215 x 60mm



### **LARGE RECTANGLE**

5 1/8 x 7 1/4 x 2 3/8"  
130 x 185 x 60mm



### **RECTANGLE**

5 1/8 x 6 1/2 x 2 3/8"  
130 x 165 x 60mm



### **SMALL RECTANGLE**

5 1/8 x 5 3/4 x 2 3/8"  
130 x 145 x 60mm



### **SQUARE**

5 1/8 x 5 1/8 x 2 3/8"  
130 x 130 x 60mm


5 UNIT RANDOM BUNDLE

## EDGE DETAILS



ROUNDED EDGE

## LAYING PATTERNS



\*Colour selection should be chosen from actual samples.

**TECHNICAL INFORMATION**

**ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units**

Conforms to:

- C140 for Absorption 5% avg - 7% max
- C140 for Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

*Test results available upon request*

**Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines**

**LEED INFORMATION**

**Materials & Resources: LEED V4:**

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

**TECHNICAL ADVANTAGES**

**ELEGANCE™**

Deep rich colours and unique textures

**REALA™**

Cast from historic European cobblestones

**ULTIMA™**

Up to 4x stronger than poured-in-place concrete

**DRIVE FRIENDLY**

Random Bundle can handle vehicular loads

*Ask about our base stabilization system*

**PRODUCT DATA**

| Stones & Bundling        | Unit Thickness | SqFt Per |       |         |       | Per Bundle |          | Soldier LnFt Per |       |        | Sailor LnFt per |       |        | Units Per |       |        | Lbs Per |        |        |
|--------------------------|----------------|----------|-------|---------|-------|------------|----------|------------------|-------|--------|-----------------|-------|--------|-----------|-------|--------|---------|--------|--------|
|                          |                | Bundle   | Layer | Section | Stone | Layers     | Sections | Unit             | Layer | Bundle | Unit            | Layer | Bundle | SqFt      | Layer | Bundle | Unit    | Layer  | Bundle |
| <b>Ayr Manufacturing</b> |                |          |       |         |       |            |          |                  |       |        |                 |       |        |           |       |        |         |        |        |
| Random Bundle            |                | 98.30    | 12.29 | -       | 0.26  | 8          | -        | -                | -     | -      | 0.444           | -     | 221.50 | 3.91      | 48    | 384    | 6.06    | 290.75 | 2,326  |
| XL Rectangle             | 2 3/8" (60mm)  | -        | -     | -       | 0.30  | -          | -        | -                | -     | -      | 0.69            | -     | 90.29  | 3.32      | -     | 128    | -       | -      | -      |
| Large Rectangle          | 2 3/8" (60mm)  | -        | -     | -       | 0.26  | -          | -        | -                | -     | -      | 0.60            | -     | 38.85  | 3.86      | -     | 64     | -       | -      | -      |
| Rectangle                | 2 3/8" (60mm)  | -        | -     | -       | 0.23  | -          | -        | -                | -     | -      | 0.54            | -     | 34.65  | 4.33      | -     | 64     | -       | -      | -      |
| Small Rectangle          | 2 3/8" (60mm)  | -        | -     | -       | 0.20  | -          | -        | -                | -     | -      | 0.48            | -     | 30.45  | 4.93      | -     | 64     | -       | -      | -      |
| Square                   | 2 3/8" (60mm)  | -        | -     | -       | 0.18  | -          | -        | -                | -     | -      | 0.43            | -     | 27.30  | 5.50      | -     | 64     | -       | -      | -      |

Notes: Sold in full bundles only on a refundable skid. All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

**APPLICATIONS**



Pedestrian



Residential Vehicular



Borders and Accents



\*Wall pairing suggestion- U-CARA™

**RECOMMENDED SANDS**



**Romex: Rompox™ ECO-Fine**  
Pedestrian Applications only

- | Ready mixed and easy to use
- | Resin film free
- | Resistant to ants, weeds, de-icing salts
- | Made from 98% natural, recycled or renewable raw materials
- | Pressure washer safe
- | Ideal for joint widths from 5mm (1/4")

**Coverage:**

| Colour                        | 5-6mm Joints         |
|-------------------------------|----------------------|
| Beige, Stone Grey, Anthracite | 125 sqft / 55 lb mix |
| 55 lb bag / 1 kg can          |                      |



**Romex: Rompox™ Flex Joint**  
Vehicular Applications (unbonded)

- | Exclusive viscous elastic jointing mortar
- | Suitable for vehicular rated and unbonded surfaces
- | Water permeable
- | Pressure washer safe
- | Self compacting and water emulsifiable during installation
- | Designed to work in combination with the ISATec™ displacement protection system

**Coverage:**

| Colour                      | Up to 14mm Joints    |
|-----------------------------|----------------------|
| Neutral, Stone Grey, Basalt | 125 sqft / 55 lb bag |
| 55 lb bag / 1 kg can        |                      |



**Alliance Gator Nitro Joint Sand**  
Pedestrian Applications only

- | Ready mixed and easy to use
- | Permeable
- | Apply rain or shine
- | Hardens from top to bottom up to 2 3/8" (60mm)
- | Must be installed above 37°F (3°C)
- | Avoid power washing for 28 days after application
- | Ideal for joint widths from 3mm (1/8")

**Coverage:**

| Colour                             | 3 mm Joints        |
|------------------------------------|--------------------|
| Beige, Silver, 40 lb bag / 18.1 kg | 84 sqft / 40lb bag |
| Black                              | 74 sqft            |
| Grey                               | 79 sqft            |



**Eurostone Bond**  
Pedestrian & Vehicular Applications

- | Setting time - 24 hours without rain for non-drainage base systems
- | Setting time - 1 hour without rain for drainage base systems
- | Sets above 32° F/ 0° C
- | Ideal for cobblestone and natural stone joints up to 1.5" (3.75cm)
- | One colour: Slate Grey

**Coverage:**

| Size      | Narrow Joints | Wide Joints  |
|-----------|---------------|--------------|
| 50 lb bag | 65 - 85 sqft  | 22 - 42 sqft |

\*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.

