

Mondrian® Plus 50 Slab



Do not use vibrating plate



1 bag of sand covers approx. 186 ft²




Pedestrian - Designed to withstand pedestrian traffic


Mondrian® Plus 50 Slab

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
	A	50 x 190 x 380	2 x 7 1/2 x 15	PRESTIGE COLOURS	
	B	50 x 380 x 380	2 x 15 x 15	12052842 Range Margaux Beige	
	C	50 x 380 x 570	2 x 15 x 22 7/16	STANDARD COLOURS	
Weight/unit (avg.)	16 kg	35 lb	12052843 Range Norvick Grey		
Surface/unit (moy.)	0.14 m ²	1.45 ft ²	12052841 Range Newport Grey		
Area/layer	1.08 m ²	11.66 ft ²	Sold in full cubes only Production location Metcalfe		
Area/cube	10.80 m²10 Rows	116.60 ft²			
Qty/cube	A = 30 B = 30 C = 20				
Weight/cube	1288 kg	2833 lb			

LAYING PATTERNS



Linear



Modular

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 50 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.