## BRISTOL VALLEY® 60mm









**GRANITE FUSION** 

OAK BROWN FUSION **NEW** 

### **VISUAL APPEARANCE**

Gentle surface clefts and waved edges.

#### **FINISH**

The subtle surface texture and understated edge detail of Bristol Valley\* brings a refined elegance to projects where a more commonplace flagstone slab may have been used in the past.

#### PRODUCT SPECIFICATIONS



LARGE RECTANGLE 15 x 22½ x 2¾" 380 x 570 x 60 mm



**SQUARE** 15 x 15 x 23/8" 380 x 380 x 60mm



**SMALL RECTANGLE** 7 ½ x 15 x 2¾" 190 x 380 x 60mm

**3 UNIT RANDOM BUNDLE** 

#### **EDGE DETAILS**



WAVED EDGE

#### **BUNDLE** CONFIGURATION



#### LAYING PATTERNS



BRISTOL VALLEY RANDOM A 40% Large Rectangle, 40%



BRISTOL VALLEY RANDOM B 40% Large Rectangle, 40% Square, 20% Small Rectangle Square, 20% Small Rectangle

<sup>\*</sup>Colour selection should be chosen from actual samples.

ENDURACOLOR" | BRISTOL VALLEY®

#### **TECHNICAL INFORMATION**

#### ASTM C 936 Standard Specifications for Solid Concrete **Interlocking Paving Units**

Conforms to

- C140 for Absorption 5% avg 7% max
- C140 for Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy +/- 3 mm

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

#### LEED INFORMATION

#### Materials & Resources: LEED V4:

Building Product Disclosure and Optimization Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • 1 point Sourcing of Raw Materials - Leadership Extraction Practices• 1 point

Material Ingredient Reporting - Material Ingredient Reporting • 1 point  ${\sf Material\ Ingredient\ Reporting\ -\ Material\ Ingredient\ Optimization\ \bullet\ 1\ point}}$ 

Environmental Product Declaration • 1 point

#### **TECHNICAL ADVANTAGES**

#### ENDURACOLOR"

Refined surface and long-lasting colour

#### PEDESTRIAN FRIENDLY

Not recommended for vehicular

#### PRODUCT DATA

	Unit	SqFt Per		Per Bundle		Soldier LnFt per		Sailor LnFt per		Units Per			Lbs Per						
Stones & Bundling	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Layer	Bundle	Unit	Layer	Bundle	SqFt	Layer	Bundle	Unit	Layer	Bundle
Pickering Manufacturing																			
Random Bundle		104.9	11.66	-	1.46	9	-	-	-	-	0.90	9.35	84.15	0.69	8	72	35.68	319.8	2,878.20
Large Rectangle	2%" (60 mm)	-	-	-	2.09	-	-	-	-	-	1.88	-	-	0.48		18	-	-	-
Square	2%" (60 mm)	-	-	-	1.40	-	-	-	-	-	1.25	-	-	1.43	-	27	-	-	-
Small Rectangle	2¾" (60 mm)	-	-	-	0.70	-	-	-	-	-	0.63	-	-	0.72		27	-	-	-

Notes: Product sold in full bundles only on a refundable skid. All measurements are nominal. Product is not intended for vehicular applications. Important: A urethane rubber paver mat must be used to prevent scuffing. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

#### **APPLICATIONS**



Pedestrian



Roof Deck



\*Wall pairing suggestion- U-CARA\* - matching colour and finish

# **RECOMMENDED SANDS**

#### Romex: Rompox\* ECO-Fine

Pedestrian Applications only

- Vehicular when laid on a Trass Bed Ready mixed and easy to use
- Resin film free
- Resistant to ants, weeds, de-icing salts Made from 98% natural, recycled or
- renewable raw materials
- Pressure washer safe
- Ideal for joint widths from 5mm (1/4")

#### Coverage:

Colour	5-6mm Joints
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix

#### Alliance - Gator G2 MAXX Sand

- Rain safe after 15 minutes (24hr no rain if concrete overlay)
- Sets above 32° F/ 0° C may vary depending on weather, drainage, bedding materials and installation
- Dust free and haze free
- Requires only one watering
- Four colours: Beige, Grey, Black and Ivory

#### Coverage:

Colour	Narrow Joints	Wide Joints			
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft			
Black 50 lb bag	58-76 sqft	20-38 sqft			

#### **RECOMMENDED SEALER**



#### Alliance - Gator Natural Look Sealer

- Water-based
- Zero aloss finish
- Multi purpose
- Rain safe after 24 hours

#### Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L / 5.28 U.S. gal.	875 sqft

<sup>\*</sup>Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.