

# ECO-PROMENADE®

ENDURACOLOR™ PERMEABLE



OPAL BLEND

Other finishes available: Il Campo®, Series™ & Umbriano®.



## VISUAL APPEARANCE

Long, linear look and feel for any contemporary permeable application.

## FINISH

By special order, you may select from a variety of standard and architectural finishes; Premier (*smooth*), Il Campo® (*brushed*), Series™ (*exposed aggregate*) and Umbriano® (*mottled*).

## PRODUCT SPECIFICATIONS



27/8 x 12 x 4"  
75 x 300 x 100mm

## EDGE DETAIL



ROUNDED EDGE

## LAYING PATTERNS



## PERMEABLE PAVEMENT DATA

Small: 1/4" Joint	JOINT MATERIAL	JOINT WIDTH*	VOID SPACE*	SURFACE INFILTRATION RATE**	MIN. INFILTRATION RATE FOR RAINFALL OF:			
					2" / HR	4.5" / HR	6.5" / HR	11" / HR
	ASTM #9 SEK Chip	7mm	10.12%	934" / HR	20	44	64	109

\*Joint Width is measured at the top of the paver. Void Space is calculated at the base of the paver. \*\*Infiltration rate is based on testing done when first installed and is an approximate. Permeable spacers are available for use with extended range of Unilock products.

\*Colour selection should be chosen from actual samples.

**TECHNICAL INFORMATION**

**ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units**

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

*Test results available upon request*

**Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines**

**SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS**

Product	Solar Reflectance	SRI
Opal Blend	0.32	34 

**LEED INFORMATION**

**Materials & Resources: LEED V4:**

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

**TECHNICAL ADVANTAGES**

**ENDURACOLOR™**

Refined surface and long-lasting colour

**DRIVE FRIENDLY**

Can handle vehicular loads  
*Ask about our base stabilization system*

 **PERMEABLE**





Can be installed to allow water to flow through



**PRODUCT DATA**

Stones & Bundling	Unit	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per			
	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Section	Bundle	Layer	Section	Bundle
<b>Georgetown Manufacturing</b>																			
2 7/8" x 12" Permeable	4" (100mm)	53.28	10.66	-	0.24	5	-	0.25	-	54.13	0.92	-	216.50	4.13	-	220	488	-	2,439





Notes: **Sold in full bundles only and is produced and sold on a required, refundable skid.** Custom finish and colour options are available. **Special order - lead time is required.** Minimum quantities apply. \*Weights vary depending on plant of manufacture & finish. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For permeable installations, Unilock recommends using granite chips for joint filler. All measurements are nominal. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

**APPLICATIONS**

 Permeable (Heavy Duty)
  Pedestrian
  Residential Vehicular
  Commercial Vehicular

 Borders and Accents
  \*Wall pairing suggestion- U-CARA® Wall -matching colour and finish

**RECOMMENDED SANDS**

 <p><b>Romex: Rompox® Pure Patio</b> Pedestrian Applications only</p> <ul style="list-style-type: none"> <li>Resin film-free</li> <li>Highly water permeable</li> <li>Resistant to ants, weeds, de-icing salts</li> <li>Pressure washer safe</li> <li>Ideal for joint widths from 5mm (1/4")</li> <li>Ideal for Residential patios and walkways</li> <li>Three colours: Neutral, Stone Grey and Basalt</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>7mm Joints</th> </tr> </thead> <tbody> <tr> <td>Neutral, Stone Grey, Basalt <i>55 lb bag / 1 kg can</i></td> <td>20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i></td> </tr> </tbody> </table>	Colour	7mm Joints	Neutral, Stone Grey, Basalt <i>55 lb bag / 1 kg can</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>	 <p><b>Romex: Rompox® Drain</b> Vehicular Applications</p> <ul style="list-style-type: none"> <li>Resin film-free</li> <li>Highly water permeable</li> <li>Self-compacting and water emulsifiable</li> <li>Resistant to ants, weeds, de-icing salts</li> <li>Pressure washer safe</li> <li>Ideal for joint widths from 3mm (1/4")</li> <li>Ideal for driveways, parking spaces and all vehicular loading applications up to 3.5 T</li> <li>Three colours: Neutral, Stone Grey and Basalt</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>7mm Joints</th> </tr> </thead> <tbody> <tr> <td>Neutral, Stone Grey, Basalt <i>Two 1 L bottles to be mixed with one 55 lb bag of Romex approved sand</i></td> <td>20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i></td> </tr> </tbody> </table>	Colour	7mm Joints	Neutral, Stone Grey, Basalt <i>Two 1 L bottles to be mixed with one 55 lb bag of Romex approved sand</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>	 <p><b>Romex: Rompox® D1</b> Heavy Duty Vehicular Applications</p> <ul style="list-style-type: none"> <li>Light to medium vehicle rated</li> <li>Increased pouring capacity that is self-compacting and water emulsifiable</li> <li>Resistant to ants, weeds, de-icing salts</li> <li>Pressure washer safe</li> <li>Ideal for joint widths from 3mm (1/8")</li> <li>Ideal for driveways, parking spaces and all vehicular loading applications up to 7.5 T</li> <li>Three colours: Neutral, Stone Grey and Basalt</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>7mm Joints</th> </tr> </thead> <tbody> <tr> <td>Neutral, Stone Grey, Basalt <i>Two 1.5 L bottles to be mixed with one 55 lb bag of Romex approved sand</i></td> <td>20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i></td> </tr> </tbody> </table>	Colour	7mm Joints	Neutral, Stone Grey, Basalt <i>Two 1.5 L bottles to be mixed with one 55 lb bag of Romex approved sand</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>	 <p><b>Alliance Gator Aqua Rock</b> Residential &amp; Commercial Applications</p> <ul style="list-style-type: none"> <li>For permeable paver joints</li> <li>Helps prevent erosion due to climatic conditions</li> <li>Use as bedding and jointing material</li> <li>Graded to meet ASTM No. 9 water rate</li> <li>Long term high infiltration performance</li> <li>2,200 lb Super Sack available for large applications</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Size</th> <th>Area</th> </tr> </thead> <tbody> <tr> <td>50 lb bag</td> <td>20-25 sqft</td> </tr> <tr> <td>2,200 lb Super Sack</td> <td>880-1100 sqft</td> </tr> </tbody> </table>	Size	Area	50 lb bag	20-25 sqft	2,200 lb Super Sack	880-1100 sqft
Colour	7mm Joints																				
Neutral, Stone Grey, Basalt <i>55 lb bag / 1 kg can</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>																				
Colour	7mm Joints																				
Neutral, Stone Grey, Basalt <i>Two 1 L bottles to be mixed with one 55 lb bag of Romex approved sand</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>																				
Colour	7mm Joints																				
Neutral, Stone Grey, Basalt <i>Two 1.5 L bottles to be mixed with one 55 lb bag of Romex approved sand</i>	20 sqft / 55 lb mix <i>(based on 1,000 sqft)</i>																				
Size	Area																				
50 lb bag	20-25 sqft																				
2,200 lb Super Sack	880-1100 sqft																				

\*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.