

Vendome® 80 and 60 Paver




Techniseal 1 bag of sand covers approx.:
Vendome 60 - 44 ft² / Vendome 80 - 33 ft²

- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Permeable - Designed to allow runoff to pass through

Vendome® 80 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
A	80 x 130 x 197	3 1/8 x 5 1/8 x 7 3/4
B	80 x 130 x 262	3 1/8 x 5 1/8 x 10 5/16
C	80 x 130 x 327	3 1/8 x 5 1/8 x 12 7/8
Weight/unit (avg.)	6 kg	12 lb
Unit/surface (avg.)	30.50 unit/m ²	2.83 unit/ft ²
Area/layer	1.05 m ²	11.28 ft ²
Area/cube	8.40 m²	8 Rows 90.24 ft²
Qty/cube	A = 88 B = 96 C = 72	
Length/row	7.86 lin. m	25.80 lin. ft
Length/cube	62.90 lin. m	206.40 lin. ft
Weight/cube	1468 kg	3236 lb


CODES	COLOURS
PRESTIGE COLOURS	
10550002	Rockland Black
10559011	Range Margaux Beige
10559012	Range Amboise Beige
STANDARD COLOUR	
10559010	Range Newport Grey
Sold in full cubes only	
Production location Bolton	




Vendome® 60 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
A	60 x 130 x 197	2 3/8 x 5 1/8 x 7 3/4
B	60 x 130 x 262	2 3/8 x 5 1/8 x 10 5/16
C	60 x 130 x 327	2 3/8 x 5 1/8 x 12 7/8
Weight/unit (avg.)	4 kg	8.5 lb
Unit/surface (avg.)	30.50 unit/m ²	2.83 unit/ft ²
Area/layer	1.05 m ²	11.28 ft ²
Area/cube	8.40 m²	8 Rows 90.24 ft²
Length/row	8.19 lin. m	26.87 lin. ft
Length/cube	65.52 lin. m	214.96 lin. ft
Weight/cube	1013 kg	2233 lb


CODES	COLOURS
PRESTIGE COLOURS	
10554763	Rockland Black
10554761	Range Margaux Beige
STANDARD COLOUR	
10554762	Range Newport Grey
Sold in full cubes only	
Production location Bolton	



LAYING PATTERNS



Linear



Modular

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vendome Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).