

BRUSSELS BLOCK[®]

CLASSIC



COFFEE CREEK



LIMESTONE



MAHOGANY



SANDSTONE

MIDNIGHT CHARCOAL
XL, Standard and Fullnose only

VISUAL APPEARANCE

The original tumbled paver. Timeless warmth, relaxed appearance.

FINISH

Tumbled and weathered.

PRODUCT SPECIFICATIONS



XL STONE
8½ x 13¾ x 2¾"
208 x 348 x 70mm



STANDARD STONE
6" x 8½ x 2¾"
173 x 208 x 70mm



HALF STONE
4½ x 6½ x 2¾"
104 x 173 x 70mm



FULLNOSE COPING
5⅞ x 11⅞ x 2¾"
150 x 300 x 70mm

*Limestone, Sandstone and
Midnight Charcoal only*


*Please see Steps, Treads and
Coping section, page 162 for
more details.*

EDGE DETAILS




TUMBLED EDGE


LAYING PATTERNS




BRUSSELS AF
40% XL, 40% Standard,
20% Half



BRUSSELS O
33% Half Stone, 67%
Standard



BRUSSELS P
67% Standard, 33% Half



BRUSSELS W
18% Half Stone, 23%
Standard, 59% XL

*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C936 Standard Specifications for Solid Concrete Interlocking Paving Units



Conforms to:

- C140 for Absorption 5% avg - 7% max
- C140 for Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Limestone	0.28	29 
Sandstone	0.41	46 

LEED INFORMATION

Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

TECHNICAL ADVANTAGES

CLASSIC

Budget-friendly. Utilizes a traditional product mix of large and small aggregates that's consistent from top to bottom with colour mixed throughout

ANTIQUED FINISH

Distressed, timeworn finish

DRIVE FRIENDLY

Can handle vehicular loads
Ask about our base stabilization system

PRODUCT DATA

Stones & Bundling	Unit Thickness	SqFt Per					Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per		
		Bundle	Layer	Sections	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Sections	Bundle	Layer	Section	Bundle	
Ayr Manufacturing																				
XL	2¾" (70mm)	95.94	11.99	31.98	0.80	8	3	0.70	27.30	81.90	1.43	45.70	137.00	1.25	40	120	378	1,008	3,024	
Standard	2¾" (70mm)	95.94	11.99	15.99	0.40	8	6	0.58	22.70	136.20	0.70	27.30	163.80	2.50	40	240	383	510	3,064	
Half	2¾" (70mm)	99.79	12.47	14.26	0.20	8	7	0.34	24.57	172.00	0.58	42.04	294.28	5.05	72	504	399	446	3,124	
Fullnose	2¾" (70mm)	96.00	12.00	24.00	0.50	8	4	0.51	23.60	96.00	-	-	-	2.00	48	192	355	710	2,841	

Notes: All measurements are nominal. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



Pedestrian



Residential Vehicular



Borders and Accents



Wall pairing suggestion- Brussels Dimensional Stone - matching colour and finish

RECOMMENDED SANDS

RECOMMENDED SEALER



+



Romex: Rompox® Fugensand
Pedestrian, Vehicular and Heavy Duty Vehicular Applications

- | Manufactured from natural, raw materials
- | Allows for efficient stormwater management and more durable paver joint
- | Quick application
- | Self-repairing properties
- | Suitable for all load classes
- | No cement haze/residue due to natural polymer binders

Coverage:

Colour	3mm Joints
Neutral, Stone Grey, Basalt <i>1 L / 5 gal</i>	50-150 sqft / 55 lb bag

Romex: Rompox® D7000 Joint Strengthener & Surface Sealer
Pedestrian, Vehicular and Heavy Duty Vehicular Applications

- | All-in-one strengthener & sealer
- | Eco-Friendly
- | Protects against dirt, oil, corrosion from climate exposure, de-icing salts
- | Protects against weed growth and wash outs
- | Allows for light surface pressure washing once cured

Coverage:

Colour	3-4mm Joints
Neutral, Stone Grey, Basalt <i>55 lb bag / 1 kg can</i>	50-150 sqft / 55 lb mix

Alliance - Gator G2 Super Sand

- | Rain safe after 1 hour (no concrete overlays)
- | Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation
- | Can be used for joints up to a max of 2"
- | Dust free and haze free
- | Requires only one watering
- | Two colours: Beige, Slate Grey

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Slate Grey <i>50 lb bag</i>	65-85 sqft	22-42 sqft

Alliance - Gator Natural Look Sealer

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L / 5.28 U.S. gal.	875 sqft

*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.