


# Esbelto™ Textureguard Paver



**Techniseal** 1 bag of sand covers approx. 124 ft<sup>2</sup>

- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic

## Esbelto™ Textureguard Large Rectangle Paver




	DIMENSIONS (MM)	DIMENSIONS (IN)
	80 x 305 x 610	3 1/8 x 12 x 24
Weight/unit	37 kg	81 lb
Unit/surface	5.382 unit/m <sup>2</sup>	0.50 unit/ft <sup>2</sup>
Area/layer	1.11 m <sup>2</sup>	12.00 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.88 m<sup>2</sup> Rows</b>	<b>96.00 ft<sup>2</sup></b>
Length/row Soldier	1.83 lin. m	6.00 lin. ft
Length/cube Soldier	14.64 lin. m	48.00 lin. ft
Qty/cube	48 units	48 units
Weight/cube	1764 kg	3888 lb


CODES	COLOURS
10551027	Marbella
10551024	Silverstone
10550536	Hickory

Sold in full cubes only  
Production location Metcalfe


TYPICAL ROW




### LAYING PATTERNS




Checkerboard



Running Bond



Offset 1/3



Herringbone

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Esbelto Textureguard Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).