




AQUASTORM

DESCRIPTION: Paver **TEXTURE:** Smooth

PALLET OVERVIEW



Aqua Storm paver meet and exceeds the requirements of ASTM C1319 for Concrete Grid Paving Units.

NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.


See page 30 for more information about applications.

JOINT WIDTH: 1 5/8" (41 mm)
% OF SURFACE OPENING: 38 %
INFILTRATION RATE: 2 395 in./hr
 (60 842 mm/hr)

WINTER CONDITIONS


De-icing salts should never be used on grass as salt will damage it. The snowblower blade should be set to leave a 3/4 to 1 1/2 in. (2 to 4 cm) tamped snow cover to protect the grass from extreme cold and prevent it from being torn off during snow removal.

Specifications per pallet		Imperial	Metric
Cubing		78.39 ft²	7.28 m ²
Approx. Weight		2 245 lbs	1 018 kg
Number of rows		7	
Coverage per row		11.20 ft ²	1.04 m ²
Linear coverage per row	Depth	13.39 lin. ft	4.08 lin. m
	Length	6.69 lin. ft	2.04 lin. m




Unit dimensions	in	mm	Units/pallet
Height	3 15/16	100	56 units
Width	10 1/16	255	
Length	20 1/16	510	


01 | Linear pattern




02 | Linear pattern



03 | Herringbone pattern



04 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Grey



Grey

