




BLU 80 mm

DESCRIPTION: Paver **TEXTURE:** Polished

PALLET OVERVIEW

















NOTES

Polished products are available on order only.

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.


See page 30 for more information about applications.

JOINT WIDTH: 9/32" (7 mm) % OF SURFACE OPENING: 3.0 % INFILTRATOIN RATE: 570 in./hr (14 475 mm/hr)

Polished is made-to-order, minimum order of 500 sq. ft. Deposit required.

Specifications per pallet		Imperial	Metric	
POLISHED	Cubing	84.96 ft ²	7.90 m ²	
	Approx. Weight	3 042 lbs	1 380 kg	
	Number of rows	8		
	Coverage per row	10.62 ft ²	0.99 m ²	
	Linear coverage per row	9.75 lin. ft	2.97 lin. m	

Н Л-	Unit dir		in	mm	Units/pallet
H A		Height	3 1/16	78	32 units
	1	Width	13	330	
	I PROPERTY.	Length	6 ½	165	
В					
D		Height	3 1/16	78	32 units
		Width	13	330	
	THE PERSON	Length	13	330	
(
0		Height	$3\frac{1}{16}$	78	16 units
		Width	13	330	
	100	Length	19 ½	495	



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

