

Mondrian® Plus 80 Paver




Techniseal 1 bag of sand covers approx. 43 ft²

- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Permeable - Designed to allow runoff to pass through


Mondrian® Plus 80 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A	80 x 165 x 330	3 1/8 x 6 1/2 x 13	PRESTIGE COLOURS		
B	80 x 330 x 330	3 1/8 x 13 x 13	10551159	Range Margaux Beige	
C	80 x 330 x 495	3 1/8 x 13 x 19 1/2	10551158	Range Amboise Beige	
Weight/unit (avg.)	18 kg	40 lb	10550461	Range Scandina Grey	
Unit/surface (avg.)	9.17 unit/m ²	0.85 unit/ft ²	STANDARD COLOURS		
Area/layer	0.98 m ²	10.55 ft ²	10551156	Range Norvick Grey	
Area/cube	8.82 m²	9 Rows	94.95 ft²	10551160	Range Newport Grey
Qty/cube	A = 36	B = 36	C = 18	Sold in full cubes only	
Length/row	2.97 lin. m	9.75 lin. ft	Production location Bolton		
Length/cube	26.73 lin. m	87.75 lin. ft			
Weight/cube	1680 kg	3704 lb			

LAYING PATTERNS



Linear



Modular

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).