# WINDERMERE® FLAGSTONE







**CLIFFSIDE GREY** 

**GRANITE BLEND** 



**IRISH COAST** 

#### **VISUAL APPEARANCE**

Gentle surface clefts and clean edges.

#### **FINISH**

Flagstone finish.

#### **PRODUCT SPECIFICATIONS**



**LARGE RECTANGLE** 14½ x 2½" 360 X 540 x 70mm



**SQUARE** 14½6 x 14½6 x 2¾″ 360 x 360 x 70mm



**SMALL RECTANGLE** 7½ x 14½ 6 x 2¾" 180 x 360 x 70mm

**3 UNIT RANDOM BUNDLE** 

#### **EDGE DETAILS**

#### **BUNDLE CONFIGURATION**



WAVED EDGE



#### LAYING PATTERNS





<sup>\*</sup>Colour selection should be chosen from actual samples.

#### **TECHNICAL INFORMATION**

#### ASTM C936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- · C140 for Absorption 5% avg 7% max
- · Compressive Strength > 7,200 PSI avg.
- · C67 for Freeze-thaw Durability
- · C418 for Abrasion Durability
- Dimensional Accuracy +/- 3mm

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

#### LEED INFORMATION

#### Materials & Resources: LEED V4:

Building Product Disclosure and Optimization

Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • 1 point

Sourcing of Raw Materials - Leadership Extraction Practices • 1 point Material Ingredient Reporting - Material Ingredient Reporting • 1 point

Material Ingredient Reporting - Material Ingredient Optimization • 1 point

Environmental Product Declaration • 1 point

#### **TECHNICAL ADVANTAGES**

#### **CLASSIC**

Budget-friendly. Utilizes a traditional product mix of large and small aggregates that's consistent from top to bottom with colour mixed throughout

#### **DRIVE FRIENDLY**

Can handle vehicular loads

Ask about our base stabilization system

#### PRODUCT DATA

	Unit		SqFt Per		Per	Sol	dier LnFt	Per	Sa	ilor LnFt	per		Units Per			Lbs Per	
Stones & Bundling	Thickness	Bundle	Layer	Stone	Layers	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Section	Bundle	Layer	Section	Bundle
Ayr Manufacturing																	
Random Bundle		98	12.25	1.35	8	-	-	-	1.17	-	84.00	0.74	-	72	392	-	3,138
Large Rectangle	2¾" (70mm)	-	-	2.09	-	-	-	-	1.77	-	42.50	0.48	-	24	-	-	-
Small Rectangle	2¾" (70mm)	-	-	0.70	-	-	-	-	0.59	-	14.20	1.43	-	24	-	-	-
Square	2¾" (70mm)	-	-	1.40	-	-	-	-	1.18	-	28.30	0.72	-	24	-	-	-

Notes: Acceptable for driveways and walkways. Product sold in full bundles only on a refundable skid. Important: A urethane rubber paver mat must be used to prevent scuffing. All measurements are nominal. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

#### **APPLICATIONS**



Pedestrian



Residential Vehicular



\*Wall pairing suggestion- Pisa Smooth™

#### **RECOMMENDED SANDS**



## Rompox: Romex\* Fugensand

- Pedestrian, Vehicular and Heavy **Duty Vehicular Applications** | Manufactured from natural, raw
- materials Quick application
- Self-repairing properties
- Suitable for all load classes
- No cement haze/residue due to natural polymer binder
- Three colours: Natural, Stone Grev and Basalt

#### Coverage:

Colour	5-6mm Joints
Neutral, Stone Grey, Basalt 1 L / 5 gal	50-150 sqft / 55 lb bag



#### Rompox: Romex D7000 Joint Strengthener & Surface Sealer

edestrian, Vehicular and Heavy

- **Duty Vehicular Applications**
- All-in-one strengthener & sealer **Eco-Friendly**
- Protects against dirt, oil, corrosion from climate exposure, de-icing salts
- Protects against weed growth and wash outs

#### Coverage:

Colour	3-4mm Joints			
Neutral, Stone	50-150			
Grey, Basalt	sqft /			
55 lb bag / 1 kg can	55 lb mix			

### Alliance Gator G2 Super Sand

- Rain safe after 1 hour (no concrete overlays)
- Sets above 32 $^{\circ}$  F/ 0 $^{\circ}$  C may vary depending on weather, drainage, bedding materials and installation
- Can be used for joints up to a max of 2"
- Dust free and haze free
- Requires only one watering
- | Two colours: Beige, Slate Grey

#### Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Slate Grey 50 lb bag	65-85 sqft	22-42 sqft

### **RECOMMENDED SEALER**



#### Alliance Gator Hybrid Low Gloss + Colour Enhancer

- Water-based
- Low gloss finish
- Vibrant Colour Enhancer
- Rain safe after 24 hours

#### Coverage:

Size	Area
3.78 L / 1 U.S. gal.	200 sqft
18.9 L / 5.28 U.S. gal.	1,000 sqft

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.

<sup>\*</sup>Please refer to Sands & Sealers on pages 190-202 for more detailed information.