

TOWN HALL®

Exclusive to **UNILOCK**



ELEGANCE **PERMEABLE**



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK



3 COLOUR BLEND

Blended on site

VISUAL APPEARANCE

The substantial proportions and unique colour blending of Town Hall® is modelled after historic North American clay street pavers. The timeless look of Town Hall® can be installed in either traditional or permeable applications for vehicular, heavy duty and pedestrian applications. The result is vintage, streetscape charm that stands the test of time.

FINISH

Town Hall® textures are cast from a multitude of different surfaces using Reala™ Technology, and Ultima™ Technology to create superior durability of this cobblestone appearance.

PRODUCT SPECIFICATIONS



STANDARD


4" x 9¾" x 2¾"
100 x 250 x 70mm

EDGE DETAILS




ROUNDED EDGE

LAYING PATTERNS



TOWN HALL A
100% Standard



TOWN HALL B
100% Standard

PERMEABLE PAVEMENT DATA

					MIN. INFILTRATION RATE FOR RAINFALL OF:			
ADA COMPLIANT	Joint Material	Joint Width*	Void Space*	Surface Infiltration Rate**	2" / HR	4.5" / HR	6.5" / HR	11" / HR
Medium: ¼" - ⅜" Joint	Kafka - 1/8 to 3/16"	9mm	6.5%	784" / HR	31	69	100	169

*Joint Width is measured at the top of the paver. Void Space is calculated at the base of the paver. **Infiltration rate is based on testing done when first installed and is an approximate. Permeable spacers are available for use with extended range of Unilock products.

*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

LEED INFORMATION

Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

TECHNICAL ADVANTAGES

ELEGANCE
Deep, rich colours with unique textures

REALA™
Cast from historic brick

ULTIMA™
Up to 4x stronger than poured-in-place concrete

DRIVE FRIENDLY
Can handle vehicular loads
Ask about our base stabilization system

PERMEABLE
Can be installed to allow water to flow through

EasyClean™
Factory sealed for integral stain resistance

PRODUCT DATA

Stones & Bundling	Unit Thickness	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per		
		Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Section	Bundle	Layer	Section	Bundle
Ayr Manufacturing																			
Standard	2¼ (70mm)	88.41	11.05	-	0.28	8	-	0.34	-	104.99	0.82	-	262.50	3.62	-	320	361	-	2,888

Notes: Sold in full bundles only on a refundable skid. All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS

- Pedestrian
- Residential Vehicular
- Commercial Vehicular
- Permeable
- Borders and Accents
- *Wall pairing suggestion- U-CARA™ Wall or Lineo™ Dimensional Stone

RECOMMENDED SANDS

RECOMMENDED SEALER



Romex: Rompox® ECO-Fine
Pedestrian Applications only

- Ready mixed and easy to use
- Resin film free
- Resistant to ants, weeds, de-icing salts
- Made from 98% natural, recycled or renewable raw materials
- Pressure washer safe
- Ideal for joint widths from 5mm (1/4")

Coverage:

Colour	5-6mm Joints
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix



Romex: Rompox® Drain
Vehicular Applications

- Resin film-free
- Highly water permeable
- Self-compacting and water emulsifiable
- Resistant to ants, weeds, de-icing salts
- Pressure washer safe
- Ideal for joint widths from 3mm (1/4")
- Ideal for driveways, parking spaces and all vehicular loading applications up to 3.5 T
- Three colours: Neutral, Stone Grey and Basalt

Coverage:

Colour	6mm Joints
Neutral, Stone Grey, Basalt Two 1 L bottles to be mixed with one 55 lb bag of Romex approved sand	25 sqft / 55 lb mix (based on 1,000 sqft)



Alliance Gator G2 MAXX Sand

- Rain safe after 15 minutes (24hr no rain if concrete overlay)
- Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation
- Dust free and haze free
- Requires only one watering
- Four colours: Beige, Grey, Black and Ivory

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft
Black 50 lb bag	58-76 sqft	20-38 sqft



Alliance Gator Seal Satin Look

- Solvent-based
- Low gloss finish
- Vibrant colour enhancer
- Rain safe after 90 minutes
- Helps resist corrosion from de-icing salt, ultra-violet rays effects, motor oils and grease stains

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft

*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.