


Melville® 80 Paver




Techniseal 1 bag of sand covers approx. 116 ft²

- 👤 Pedestrian - Designed to withstand pedestrian traffic
- 🚗 Vehicular - Designed to withstand car traffic


Melville® 80 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A	80 x 190 x 380	3 1/8 x 7 1/2 x 15	PRESTIGE COLOURS		
B	80 x 380 x 380	3 1/8 x 15 x 15	10550869	Range Amber Beige (2)	
C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10550446	Range Scandina Grey (1)	
Weight/unit (avg.)	27 kg	59 lb	10550447	Range Margaux Beige (1)	
Unit/surface (avg.)	7.39 unit/m ²	0.69 unit/ft ²	10554764	Range Chambord Gre (1)	
Area/layer	1.08 m ²	11.66 ft ²	10551007	Range Bayona Grey (1) - N	
Area/cube	8.64 m²	8 Rows	STANDARD COLOURS		
Length/row	3.04 lin. m	9.97 lin. ft	10550868	Range Shaded Grey (3)	
Length/cube	24.32 lin. m	79.79 lin. ft	10550558	Range Newport Grey (1)	
Weight/cube	1716 kg	3783 lb	Sold in full cubes only		
Production locations:					
(1) Cambridge					
(2) Metcalfe					
(3) St-Eustache					

LAYING PATTERNS



Linear



Herringbone

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.