


Niagara 60 and 80 Paver



Techniseal Sand 1 Bag - Approx. 82 ft² coverage

👤 Pedestrian - Designed to withstand pedestrian traffic

🚗 Vehicular - Designed to withstand car traffic


Niagara 60 Paver – Rectangle



	DIMENSIONS (MM)	DIMENSIONS (IN)
	60 x 98 x 198	2.36 x 3.86 x 7.80
Weight/unit	2.72 kg	6.0 lb
Units/area	4.58 units/ft ²	
Area/section	15.70 ft ²	
Area/cube	94.40 ft²	
Length/section	24.00 lin. ft	
Length/cube	140.40 lin. ft	
Qty	432 units/cube	
Weight	2590 lb/1174 kg/cube 432 lb/196 kg/section	

CODES	COLOURS
10500854	Natural

Sold by section
Production location Cambridge




Niagara 80 Paver – Rectangle (NON STOCK - Special order only)



	DIMENSIONS (MM)	DIMENSIONS (IN)
	80 x 98 x 198	3.15 x 3.86 x 7.80
Weight/unit	3.08 kg	7.8 lb
Units/area	4.58 units/ft ²	
Area/section	15.70 ft ²	
Area/cube	94.40 ft²	
Length/section	94.40 lin. ft	
Length/cube	132.60 lin. ft	
Qty	464 units/cube (400 rectangles, 64 half stones)	
Weight	562 lb/255 kg/section 3371 lb/1529 kg/cube	

CODE	COLOUR
10501987	Natural

Sold in full cubes only
Production location Cambridge



Niagara 80 Paver – Herringbone (NON STOCK - Special order only)




	DIMENSIONS (MM)	DIMENSIONS (IN)
	80 x 98 x 198	3.15 x 3.86 x 7.80
Weight/unit	3.54 kg	7.80 lb
Units/area	4.58 units/ft ²	
Area/cube	94.40 ft²	
Qty	464 units/cube (400 rectangles, 64 half stones)	
Weight	1529 kg 3371 lb	


CODE	COLOUR
10501980	Natural

Sold in full cubes only
Production location Cambridge


LAYING PATTERNS




Parquet
100% Rectangle



Modified Parquet
100% Rectangle



Running Bond
100% Rectangle



Herringbone
100% Rectangle

For superior results, mark off a true 90° angle before you begin laying the pavers.

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Niagara 60 and 80 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.