# BEACON HILL<sup>™</sup> FLAGSTONE 80mm **ENDURACOLOR**<sup>®</sup>



44 SRI



ALMOND GROVE FUSION

10

FOSSIL



TUSCANY

**GRANITE MIST** 

## **VISUAL APPEARANCE**

Gentle surface clefts and clean edges.

#### FINISH

Flag/Riven finish.

# **PRODUCT SPECIFICATIONS**



LARGE RECTANGLE 15 x 22½ x 3½" 380 x 570 x 80mm



SQUARE 15 x 15 x 31/8" 380 x 380 x 80mm



SMALL RECTANGLE 7½ x 15 x 3½" 190 x 380 x 80mm

**3 UNIT RANDOM BUNDLE** 

#### EDGE DETAIL



ROUNDED EDGE





LAYING PATTERNS

**BEACON HILL** 

BHF RANDOM A 40% Large Rectangle, 40% Square, 20% Small Rectangle Square, 20% Small Rectangle



BHF RANDOM B 40% Large Rectangle, 40%

\*Colour selection should be chosen from actual samples.

**UNILOCK** 

#### **TECHNICAL INFORMATION**

# ASTM C936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 4% avg 5% max
- C140 for Compressive Strength > 8,000 PSI avg.
- C1645 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy +/- 3mm Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory

Guidelines

#### SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI			
Tuscany	0.39	44 44 SRI			

#### LEED INFORMATION

#### Materials & Resources: LEED V4:

Building Product Disclosure and Optimization Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • 1 point Sourcing of Raw Materials - Leadership Extraction Practices • 1 point Material Ingredient Reporting - Material Ingredient Reporting • 1 point Material Ingredient Reporting - Material Ingredient Optimization • 1 point Environmental Product Declaration • 1 point

#### **TECHNICAL ADVANTAGES**

#### ENDURACOLOR<sup>®</sup>

Refined surface and long-lasting colour

#### DRIVE FRIENDLY

80mm pavers can handle vehicular loads Ask about our base stabilization system

#### PRODUCT DATA

	Unit	SqFt Per			Per Bundle		Soldier LnFt Per		Sailor LnFt per		Units Per		Lbs Per					
Stones & Bundling	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Layer	Bundle	SqFt	Bundle	Layer	Layer	Bundle
Fossil and Granite	Fossil and Granite Mist manufactured in Ayr / All other colours manufactured in Pickering																	
Random Bundle		81.60	11.65	-	-	7	-	-	-	-	-	8.86	65.20	0.69	56	426.59	-	2,986.1
Large Rectangle	31⁄s" (80mm)	-	4.66	-	2.33	-	-	-	-	-	1.87	-	26.25	0.48	14	-	-	-
Small Rectangle	31⁄%" (80mm)	-	2.33	-	0.77	-	-	-	-	-	0.63	-	13.23	1.29	21	-	-	-
Square	3⅓" (80mm)	-	4.66	-	1.55	-	-	-	-	-	1.25	-	26.25	0.72	21	-	-	-

Notes: Sold in full bundles only on a refundable skid. Beacon Hill 80mm is approved for vehicular applications. All measurements are nominal. Important: A urethane rubber paver mat must be used to prevent scuffing. For more information, samples or custom options, please contact your Unilock Territory

Manager or call 1-800-UNILOCK.

### APPLICATIONS



Residential Vehicular

		RECOMMEN	NDED SANDS			RECOMMENDED SEALER			
Romex: Rompox' ECO-Fine Pedestrian Applications only Ready mixed and easy to use Resin film free Resistant to ants, weeds, de-icing salts Made from 98% natural, recycled or renewable raw materials Pressure washer safe Ideal for joint widths from 5mm (1/4")		Self-compacting a Ideal for joint widt Ideal for driveways	pplications ehicle rated weeds, frost & nd water emulsifiable hs from 3mm (1/4") i, parking spaces	Alliance - Ga Rain safe after ' if concrete over Sets above 32° depending on v bedding materi Dust free and h Requires only c Four colours: B Ivory Coverage:	I5 minutes ( lay) F/ 0° C - ma veather, dra als and insta aze free ne watering	Alliance - Gator Natural Look Sealer Water-based Zero gloss finish Multi purpose Rain safe after 24 hours			
Coverage:	5-6mm Joints	Colour	7mm Joints	Colour	Narrow	Wide	Coverage:	Area	
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix	Neutral, Stone	20 sqft / 55 lb mix (based on 1,000 sqft)		Joints	Joints	3.78 L / 1 U.S. gal.	175 saft	
		Grey, Basalt Two 1 L bottles to be mixed with one		Beige, Grey, Ivory <i>50 lb bag</i>	65-85 sqft	22-42 sqft	18.9 L / 5.28 U.S. gal.	875 saft	
		55 lb bag of Romex approved sand		Black 50lb. bag	58-76 sqft	20-38 sqft	10.9 L / 5.28 U.S. gal.	oro sqit	

\*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.

11