

# PROMENADE™ PLANK PAVER

ENDURACOLOR™



OPAL BLEND  
4" x 12", 4" x 16", 8" x 24"



SANDSTONE  
4" x 12"



STEEL GREY BLEND  
4" x 12", 4" x 16", 8" x 24"



LIGHT GREY  
*IL CAMPO' FINISH*  
4" x 12", 8" x 24"



GRANITE BLEND  
*IL CAMPO' FINISH*  
4" x 12", 8" x 24"



DARK CHARCOAL  
*IL CAMPO' FINISH*  
4" x 12", 8" x 24"



BLACK GRANITE  
*SERIES™ FINISH*  
4" x 12", 8" x 24"

## VISUAL APPEARANCE

Long and narrow design facilitates a linear laying pattern resulting in a finished and sleek appearance to complement current architectural design trends, leaving no compromise on style for heavy-duty functionality.

## FINISH

Available in a variety of Unilock Select finishes such as Il Campo®, Series™ (Stock) and Umbriano® (Custom), to name a few.

## PRODUCT SPECIFICATIONS



8 x 24 x 4"  
200 x 600 x 100mm  
See Slabs section page  
98 for more details



4 x 16 x 4"  
100 x 400 x 100mm




4 x 12 x 4"  
100 x 300 x 100mm

## EDGE DETAILS



ROUNDED EDGE


## LAYING PATTERNS



PROMENADE PLANK PAVER A 8X24  
100% 8 x 24



PROMENADE PLANK PAVER C 4X16  
100% 4 x 16



PROMENADE PLANK PAVER G  
40% 8 x 24, 40% 4 x 16,  
20% 4 x 12

\*Colour selection should be chosen from actual samples.



TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

- Conforms to:
    - C140 for Absorption 5% avg - 7% max
    - Compressive Strength > 7,200 PSI avg.
    - C67 for Freeze-thaw Durability
    - C418 for Abrasion Durability
    - Dimensional Accuracy +/- 3mm
- Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Opal Blend	0.32	34 
Steel Grey Blend	0.12	9 

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour

DRIVE FRIENDLY

Can handle vehicular loads  
Ask about our base stabilization system

IL CAMPO FINISH

Graphically interesting etched lines

SERIES FINISH

Granite, Quartz and Marble surface materials

LEED INFORMATION

Materials & Resources: LEED V4:






- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • 1 point
- Sourcing of Raw Materials - Leadership Extraction Practices • 1 point
- Material Ingredient Reporting - Material Ingredient Reporting • 1 point
- Material Ingredient Reporting - Material Ingredient Optimization • 1 point
- Environmental Product Declaration • 1 point





PRODUCT DATA

Stones & Bundling	Unit	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per	
	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Bundle	Layer	Bundle
<b>Pickering Manufacturing</b>																	
8" x 24"	4" (100mm)	51.67	10.33	-	1.29	5	-	0.66	-	26.20	1.97	-	78.70	0.77	40	478	2,391
4" x 16"	4" (100mm)	51.67	10.33	-	0.43	5	-	0.33	-	39.40	1.31	-	157.50	2.32	120	488	2,440
4" x 12"	4" (100mm)	58.13	11.63	-	0.32	5	-	0.33	-	59.10	0.98	-	177.20	3.10	180	532	2,659

Notes: Sold in full bundles only on a refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing.** All measurements are nominal. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS

-  Pedestrian
-  Residential Vehicular
-  Commercial Vehicular (4 x 12 x 4" only)
-  Borders and Accents
-  \*Wall pairing suggestion- U-CARA™ Wall or Lineo™ Dimensional Stone

RECOMMENDED SANDS			RECOMMENDED SEALER																									
	+																											
<p><b>Romex: Rompox® Fugensand</b> Pedestrian, Vehicular and Heavy Duty Vehicular Applications</p> <ul style="list-style-type: none"> <li>Manufactured from natural, raw materials</li> <li>Quick application</li> <li>Self-repairing properties</li> <li>Suitable for all load classes</li> <li>No cement haze/residue due to natural polymer binder</li> <li>Three colours: Natural, Stone Grey and Basalt</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>3mm Joints</th> </tr> </thead> <tbody> <tr> <td>Neutral, Stone Grey, Basalt 1 L / 5 gal</td> <td>110 sqft / 55 lb bag 750 sqft / 5 gal drum</td> </tr> </tbody> </table>	Colour	3mm Joints	Neutral, Stone Grey, Basalt 1 L / 5 gal	110 sqft / 55 lb bag 750 sqft / 5 gal drum		<p><b>Romex: Rompox® D7000 Joint Strengtheners &amp; Surface Sealer</b> Pedestrian, Vehicular and Heavy Duty Vehicular Applications</p> <ul style="list-style-type: none"> <li>All-in-one strengthener &amp; sealer</li> <li>Eco-Friendly</li> <li>Protects against dirt, oil, corrosion from climate exposure, de-icing salts</li> <li>Protects against weed growth and wash outs</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>3mm Joints</th> </tr> </thead> <tbody> <tr> <td>Neutral, Stone Grey, Basalt 55 lb bag / 1 kg can</td> <td>110 sqft / 55 lb bag 750 sqft / 5 gal drum</td> </tr> </tbody> </table>	Colour	3mm Joints	Neutral, Stone Grey, Basalt 55 lb bag / 1 kg can	110 sqft / 55 lb bag 750 sqft / 5 gal drum	<p><b>Alliance Gator G2 MAXX Sand</b></p> <ul style="list-style-type: none"> <li>Rain safe after 15 minutes (24hr no rain if concrete overlay)</li> <li>Sets above 32° F / 0° C - may vary depending on weather, drainage, bedding materials and installation</li> <li>Dust free and haze free</li> <li>Requires only one watering</li> <li>Four colours: Beige, Grey, Black and Ivory</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>Narrow Joints</th> <th>Wide Joints</th> </tr> </thead> <tbody> <tr> <td>Beige, Grey, Ivory 50 lb bag</td> <td>65-85 sqft</td> <td>22-42 sqft</td> </tr> <tr> <td>Black 50 lb bag</td> <td>58-76 sqft</td> <td>20-38 sqft</td> </tr> </tbody> </table>	Colour	Narrow Joints	Wide Joints	Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft	Black 50 lb bag	58-76 sqft	20-38 sqft	<p><b>Alliance Gator Hybrid Low Gloss + Colour Enhancer</b></p> <ul style="list-style-type: none"> <li>Water-based</li> <li>Low gloss finish</li> <li>Vibrant Colour Enhancer</li> <li>Rain safe after 24 hours</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Size</th> <th>Area</th> </tr> </thead> <tbody> <tr> <td>3.78 L / 1 U.S. gal.</td> <td>200 sqft</td> </tr> <tr> <td>18.9 L / 5.28 U.S. gal.</td> <td>1,000 sqft</td> </tr> </tbody> </table>	Size	Area	3.78 L / 1 U.S. gal.	200 sqft	18.9 L / 5.28 U.S. gal.	1,000 sqft	
Colour	3mm Joints																											
Neutral, Stone Grey, Basalt 1 L / 5 gal	110 sqft / 55 lb bag 750 sqft / 5 gal drum																											
Colour	3mm Joints																											
Neutral, Stone Grey, Basalt 55 lb bag / 1 kg can	110 sqft / 55 lb bag 750 sqft / 5 gal drum																											
Colour	Narrow Joints	Wide Joints																										
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft																										
Black 50 lb bag	58-76 sqft	20-38 sqft																										
Size	Area																											
3.78 L / 1 U.S. gal.	200 sqft																											
18.9 L / 5.28 U.S. gal.	1,000 sqft																											

\*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.

