

# Trafalgar® 60 Paver



- 1 bag of sand covers approx. 122 ft<sup>2</sup>
- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Permeable - Designed to allow runoff to pass through


## Trafalgar® 60 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
<b>A</b>	60 x 100 x 200	2 3/8 x 3 15/16 x 7 7/8			
<b>B</b>	60 x 200 x 200	2 3/8 x 7 7/8 x 7 7/8			
<b>C</b>	60 x 300 x 200	2 3/8 x 11 13/16 x 7 7/8			
Weight/unit (avg.)	6 kg	12 lb			
Unit/surface (avg.)	25.00 unit/m <sup>2</sup>	2.32 unit/ft <sup>2</sup>			
Area/layer	1.08 m <sup>2</sup>	11.63 ft <sup>2</sup>			
<b>Area/cube</b>	<b>10.80 m<sup>2</sup></b>	<b>10 Rows</b>	<b>116.30 ft<sup>2</sup></b>		
Qty/cube	A = 80	B = 80	C = 100		
Length/row Soldier	5.40 lin. m	17.72 lin. ft			
Length/cube Soldier	54.00 lin. m	177.20 lin. ft			
Weight/cube	1466 kg	3230 lb			
			<b>PRESTIGE COLOURS</b>		
			10550441	Range Amboise Beige	
			10550442	Range Margaux Beige	
			<b>STANDARD COLOURS</b>		
			10550368	Range Norvick Grey	
			10550370	Range Newport Grey	
			Sold in full cubes only		
			Production location Bolton		


## Trafalgar® 60 Large Square Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
<b>D</b>	60 x 300 x 300	2 3/8 x 11 13/16 x 11 13/16			
Weight/unit	12 kg	27 lb			
Units/area	11.11 units/m <sup>2</sup>	1.03 units/ft <sup>2</sup>			
Area/layer	1.08 m <sup>2</sup>	11.63 ft <sup>2</sup>			
<b>Area/cube</b>	<b>10.80 m<sup>2</sup></b>	<b>10 Rows</b>	<b>116.30 ft<sup>2</sup></b>		
Length/layer	3.60 lin. m	11.80 lin. ft			
Length/cube	36.00 lin. m	118.00 lin. ft			
Qty/cube	120 units	120 units			
Weight/cube	1466 kg	3230 lb			
			10550379	Rockland Black	
			10550547	Range Amboise Beige	
			10550548	Range Margaux Beige	
			10550371	Range Norvick Grey	
			10550373	Range Newport Grey	
			Sold in full cubes only		
			Production location Bolton		


### LAYING PATTERNS




Linear  
0% Large Square



Modular  
0% Large Square



Linear - Stack Bond  
100% Large Square



Linear - Stack Bond 45°  
100% Large Square

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Trafalgar Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).