


Cassara® Paver




Techniseal 1 bag of sand covers approx.:
Mixed - 55 ft² / Large Rectangle - 62 ft²

- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic

Cassara® Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
A	100 x 300 x 400	4 x 11 13/16 x 15 3/4
B	100 x 300 x 500	4 x 11 13/16 x 19 11/16
C	100 x 300 x 600	4 x 11 13/16 x 23 5/8
Weight/unit (avg.)	35 kg	76 lb
Unit/surface (avg.)	6.67 unit/m ²	0.62 unit/ft ²
Area/layer	0.90 m ²	9.69 ft ²
Area/cube	7.20 m²	8 Rows 77.52 ft²
Qty/cube	A = 16	B = 16
Length/row	3.00 lin. m	9.84 lin. ft
Length/cube	24.00 lin. m	78.72 lin. ft
Weight/cube	1657 kg	3655 lb


CODES	COLOURS
PRESTIGE COLOURS	
10200757	Range Scandina Grey
10200561	Range Amber Beige
10200563	Rockland Black
STANDARD COLOUR	
10200562	Range Shaded Grey
Sold in full cubes only Production location St-Eustache	




Cassara® Large Rectangle Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
D	100 x 300 x 700	4 x 11 13/16 x 27 9/16
Weight/unit	48 kg	106 lb
Unit/surface	4.76 unit/m ²	0.44 unit/ft ²
Area/layer	0.63 m ²	6.78 ft ²
Area/cube	5.04 m²	8 Rows 54.24 ft²
Length/row Soldier	0.90 lin. m	2.95 lin. ft
Length/cube Soldier	7.20 lin. m	23.60 lin. ft
Qty/cube	24 units	24 units
Weight/cube	1160 kg	2557 lb


CODES	COLOURS
PRESTIGE COLOURS	
10200758	Range Scandina Grey
10200565	Range Amber Beige
10200566	Rockland Black
STANDARD COLOUR	
10200564	Range Shaded Grey
Sold in full cubes only Production location St-Eustache	




LAYING PATTERNS



Cassara 100% D Linear



Cassara 100% ABC Linear



Cassara 85% ABC / 15% D Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Cassara Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.