


Melville® 60 Slab



Do not use vibrating plate



1 bag of sand covers approx. 155 ft²



Pedestrian - Designed to withstand pedestrian traffic

Melville® 60 Slab


	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A	60 x 190 x 380	2 3/8 x 7 1/2 x 15	PRESTIGE COLOURS		
B	60 x 380 x 380	2 3/8 x 15 x 15	12053046	Range Amber Beige (1)	
C	60 x 380 x 570	2 3/8 x 15 x 22 7/16	12052365	Range Scandinia Grey (3)	
Weight/unit (avg.)	19 kg	42 lb	12052734	Range Margaux Beige (1)	
Unit/surface (avg.)	0.14 unit/m ²	1.46 unit/ft ²	12052104	Range Chambord Grey (2)	
Area/layer	1.08 m ²	11.66 ft ²	12050265	Range Bayona Grey (4) - N	
Area/cube	10.80 m²	10 Rows 116.60 ft²	STANDARD COLOURS		
Qty/cube	80 units	80 units	12053045	Range Shaded Grey (4)	
Weight/cube	1538 kg	3391 lb	12052733	Range Newport Grey (3)	

Sold in full cubes only


Production locations:

- (1) Metcalfe
- (2) Montréal
- (3) Cambridge
- (4) St-Eustache

LAYING PATTERNS



Modular



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.