




# HYDRA

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.

## CHARACTERISTICS

- Clamp or Mechanical tool available for machine installation. Check with your local Techo-Bloc representative for more information.
- 6000 to 8000 sq. ft can be installed per day with mechanical installation and a team of 5 persons

## NOTES

See page 33 and 101 for more technical information.

See page 30 for more information about applications.


**JOINT WIDTH:** 1/2" ( 13 mm)  
**% OF SURFACE OPENING:** 8.3 %  
**INFILTRATION RATE:** 605 in./hr  
 (15 345 mm/hr)

Specifications per pallet	Imperial	Metric
Cubing	<b>62 ft<sup>2</sup></b>	5.76 m <sup>2</sup>
Approx. Weight	2 811 lbs	1 275 kg
Number of rows	8	
Coverage per row	7.75 ft <sup>2</sup>	0.72 m <sup>2</sup>
Linear coverage per row	11.80 lin. ft	3.60 lin. m



Unit dimensions	in	mm	Units/pallet
Height	3 15/16	100	96 units
Width	7 7/8	200	
Length	11 13/16	300	

## 01 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

Grey

Shale Grey

