

# Vendome® 80 and 60 Paver




**Techniseal** 1 bag of sand covers approx.:  
Vendome 60 - 44 ft<sup>2</sup> / Vendome 80 - 33 ft<sup>2</sup>

- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Permeable - Designed to allow runoff to pass through

## Vendome® 80 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
<b>A</b>	A 80 x 130 x 197	3 1/8 x 5 1/8 x 7 3/4
<b>B</b>	B 80 x 130 x 262	3 1/8 x 5 1/8 x 10 5/16
<b>C</b>	C 80 x 130 x 327	3 1/8 x 5 1/8 x 12 7/8
	Weight/unit (avg.) 6 kg	12 lb
	Unit/surface (avg.) 30.50 unit/m <sup>2</sup>	2.83 unit/ft <sup>2</sup>
	Area/layer 1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>
	<b>Area/cube 8.40 m<sup>2</sup> 8 Rows 90.24 ft<sup>2</sup></b>	
	Qty/cube A = 88 B = 96 C = 72	
	Length/row 7.86 lin. m	25.80 lin. ft
	Length/cube 62.90 lin. m	206.40 lin. ft
	Weight/cube 1468 kg	3236 lb


CODES	COLOURS
<b>PRESTIGE COLOURS</b>	
10550002	Rockland Black
10559011	Range Margaux Beige
10559012	Range Amboise Beige
<b>STANDARD COLOUR</b>	
10559010	Range Newport Grey
Sold in full cubes only	
Production location Bolton	




## Vendome® 60 Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)
<b>A</b>	A 60 x 130 x 197	2 3/8 x 5 1/8 x 7 3/4
<b>B</b>	B 60 x 130 x 262	2 3/8 x 5 1/8 x 10 5/16
<b>C</b>	C 60 x 130 x 327	2 3/8 x 5 1/8 x 12 7/8
	Weight/unit (avg.) 4 kg	8.5 lb
	Unit/surface (avg.) 30.50 unit/m <sup>2</sup>	2.83 unit/ft <sup>2</sup>
	Area/layer 1.05 m <sup>2</sup>	11.28 ft <sup>2</sup>
	<b>Area/cube 8.40 m<sup>2</sup> 8 Rows 90.24 ft<sup>2</sup></b>	
	Length/row 8.19 lin. m	26.87 lin. ft
	Length/cube 65.52 lin. m	214.96 lin. ft
	Weight/cube 1013 kg	2233 lb


CODES	COLOURS
<b>PRESTIGE COLOURS</b>	
10554763	Rockland Black
10554761	Range Margaux Beige
<b>STANDARD COLOUR</b>	
10554762	Range Newport Grey
Sold in full cubes only	
Production location Bolton	



### LAYING PATTERNS



Linear



Modular

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Vendome Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).